

VANISHING OIL-V5

DESCRIPTION

VANISHING OIL-V5 is a solvent based lubricant. This product leaves a thin imperceptible film of lubricant that facilitates a clean die release of thin sheet or roll stock. The carrier generally dries in one to four hours. Normally, cleaning is not required after using this product. Lower flash facilitates quicker dry time. Does not affect most painted or plastic surfaces in most cases, spot testing is recommended.

ADVANTAGES

- Non staining
- Easily applied
- Easily removed
- Post cleaning not necessary
- Ready to use

PHYSICAL PROPERTIES

| | |
|----------------------|----------------------|
| Appearance: | <i>Water white</i> |
| Specific gravity: | <i>0.80</i> |
| Bulk density @ 60°F: | <i>6.80 lbs/gal</i> |
| Flammable limits: | <i>LEL: 1 UEL: 6</i> |
| Flash point: | <i>105° F</i> |
| Viscosity @ 100° F: | <i>37</i> |

APPLICATION

VANISHING OIL may be applied by brush, roller, spray, dip tank, slush, or flow coat.

DISPOSABILITY

Handle as you would for any petroleum based products. Spills can be cleaned up with any common oil absorbent. Do not expose to extreme temperatures due to possible drum rupture. Do not pressurize drum or reuse empty container.